

Job Name: Type: Part #: Notes:

ECARELZXTE

Chicago Approved (Recessed) Edgelit Aluminum Exit/Stairs Signs

ILLUMINATION

- · Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.
- · UV stabilized, silk screened acrylic panels provide consistent, uniform illumination.

ELECTRICAL

- Dual 120V/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V Long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 120-minuteemergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- · Compatible with drywall or drop-thru ceiling mount installations.
- · Wall mount capability optional.

HOUSING

- · Premium-grade, extruded aluminum housing.
- Extruded aluminum trim assembly is easily detachable. providing accessibility for service or maintenance. Also available in optional white finish.
- · Single or double face configurations.

ORDERING INFORMATION

OPTIONS

· WM: Wall mount.

Wall Mount option is shown in image below.

DIMENSIONS

15¾"————————————————————————————————————	→ O	<-41/8"> <-31/4">	<u> </u>
			12½"

WARRANTY / LISTING

- · Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0° 50°C).
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- · Meets city of Chicago sign and plenum requirements.
- Certified to CEC under Title 20 Regulations.

STANDARD









Sample Part Number: ECARELZXTE

PART#		No. of FACES	1	LETTER	TR	RIM PLATE	ВАТ	ΓERY	SIGNAGE / I	DIRECTIONAL ARROWS	OP	TIONS
ECARELZXTE	1	Single Face	RW	Red On	Α	Aluminum	(blank)	AC-Only	-NA	Exit No Arrow	WM	Wall
	2	Double Face		White	W	White	EM	Battery	-S-NA	Stair No Arrow		Mount 1
								Backup	-DA	Exit Double Arrow		
									-S-DA	Stair Double Arrow		
'		I		1	'	I		1	-RA1	Exit Right Arrow	'	
¹ Available in single face of	confiau	ration onlv.							-S-RA1	Stair Right Arrow		
² Available in double face	_	,							-LA	Exit Left Arrow		
									-S-LA	Stair Left Arrow		
									-LARA ²	Exit Left/Right Arrow		
5 06									-S-LARA ²	Stair Left/Right Arrow		

2025.06




Job Name:	
Type:	
Part #:	
Notes:	

ELECTRICAL INFORMATION

PART#	Input Wa	tts (W)	Input Amps (A)		
PARI#	PART#	PART#	PART#	PART#	
AC Model	PART#	PART#	PART#	PART#	
EM Model	PART#	PART#	PART#	PART#	

WALL MOUNT DIMENSIONS



ARROW CONFIGURATION

