

JOD Marrie.		
Type:		
Part #:		
Notes:		

EHLWLEZU

Hazardous Location Exit Sign

ILLUMINATION

• Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery).
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiatesbattery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Die-cast mounting brackets provided for surface wallmount installation.
- Pre-installed conduit hub for conduit and pendant-mount installations.

HOUSING


- Housing is fiberglass reinforced polycarbonate construction in gray finish.
- Corrosion-resistant enclosure with one piece, highimpact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- EZ snap-out Chevron directional indicators.

OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
- TP: Tamper-proof hardware helps discourageunauthorized access to the unit.



DIMENSIONS



ELECTRICAL INFORMATION

	CATALOG NUMBER	INPUT W	ATTS (W)	INPUT AMPS (A)		
		120	277	120V	277V	
EHLWL	.EZU-RED/GREEN/EM/SDT	3.0	3.0	0.03	0.02	

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Batteries prorated for five years.
- Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- IP66 rated for Ingress Protection.
- Rated for Class 1, Division 2, Groups A, B, C, & D.
- Certified to CEC under Title 20 Regulations.
- UL listed for wet locations (-20°C 50°C).

STANDARD











COLD



ORDERING INFORMATION

Sample Part Number: EHLWLEZU1RGEM

MODEL	No. of FACES		LETTER COLOR		HOUSING COLOR		BATTERY		OPTIONS	
EHLWLEZU	1 2	Single Double	R G	Red Green	G	Gray	(blank) EM	AC-Only NiCd Battery	SDT TP	Self-Diagnostics ¹ Tamper-Proof

2025.06 Available in EM units only.