

ELEDSDXR627

Steel Housing LED Emergency Unit

ILLUMINATION

- Long lasting, efficient, ultra bright white LED lamp heads.
- 1.5 watt (12 LEDs x 0.125 watt) per head.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provide optimal center-to-center spacing.

ELECTRICAL

- Dual 120V/277V.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V sealed lead acid, maintenance-free, rechargeable battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Remote capacity of 20W standard.
- Runs up to 8 hours without remote heads.

HOUSING


- Durable 20-gauge steel construction.
- White or black finish.

MOUNTING

- Knockouts on the back for wall mount.
- Side and top knockouts for conduit feed applications.



DIMENSIONS



WARRANTY / LISTING

- Five year warranty on all electronics and housing.
- Battery
- WSA
- T

STANDARD



ORDERING INFORMATION

Sample Part Number: ELEDSDXR627

MODEL	HOUSING COLOR	
ELEDSDXR627	(blank)	White
	B	Black

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
ELEDSDXR627	11.0	11.0	0.11A	0.04A

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY											
			MRHLED	RHLED	RH16LED	RH16		RH		RHR		SRH		SRHLED
				MV		6V	12V	6V	12V	6V	12V	6V	12V	
ELEDSDXR627	6V	20W		X	X	X		X		X		X		X