

EEM

LED Reduced Profile Thermoplastic Emergency Unit

ILLUMINATION

- Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 30-ft center-to-center spacing with 3-ft path of egress at 10-ft mounting height.
- 1.5 watt (3 LEDs x 0.50 watt) per head.
- Unique all-inclusive lamp, reflector and lens assembly.

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

OPTIONS

- RC: Remote capacity of 2.5 watts.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
- USA: Substantial transformation assembly in U.S. complies with "Assembled in USA" under the Buy American Act.
- NH: No lamp heads attached to the unit enabling it to be used as a remote capable emergency unit.

MOUNTING


- Universal knockout pattern on back plate for surface mount.
- Suitable for wall or ceiling mount.
- Knockout for conduit applications.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.



DIMENSIONS



WARRANTY / LISTING

- Five year warranty on all electronics and housing. Batteries pro rated for five years.
- UL listed for damp locations (0°C – 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Certified to CEC under title 20 regulations.

STANDARD



OPTIONAL



ORDERING INFORMATION

Sample Part Number: **EEMW**

MODEL	HOUSING COLOR		OPTIONS	
EEM	W	White	RC	Remote Capacity
	B	Black	SDT	Self-Diagnostics
			USA	Assembled in USA
			NH	No Heads

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
EEM	0.6	0.7	0.075	0.075
EEM-SDT	0.6	0.7	0.09	0.09
EEM-RC/SDT	0.8	1.0	0.12	0.12

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY			
			RHLED	MRHLED	RH16LED	SRHLED
EEM RC	3.6V	2.5W	X	X		
EEM RC NH	3.6V	5.5W	x	x		
EEM NH	3.6V	3.0W	x	x		